DERWENT-ACC-NO: 1998-313490

DERWENT-WEEK: 200018

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: ATM link statistical multiplexing method with two-level classification - provides e.g. 10 percent more virtual connections by subdivision of class characterised by more favourable results of sigma rule algorithm

INVENTOR: LAMPE, D; WALLMEIER, E

PATENT-ASSIGNEE: SIEMENS AG[SIEI]

PRIORITY-DATA: 1996DE-1049649 (November 29, 1996)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN	I-IPC	
DE 19649649 A1	June 4, 1998	N/A
007 H04I	012/56	
AU 715702 B	February 10, 2000	N/A
000 H04Q	011/04	
WO 9824260 A1	June 4, 1998	G
000 но40		
AU 9853068 A	June 22, 1998	N/A
000 но40	•	
EP 941630 A1	September 15, 1999	G
000 H04Q		
	December 15, 1999	N/A
000 но40	011/04	

DESIGNATED-STATES: AU CA CN US AT BE CH DE DK ES FI FR GB GR IE IT LU MC NL PT S E AT BE CH DE ES FR GB IT LI NL PT SE

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
DE 19649649A1	N/A	1996DE-1049649
November 29,	1996	
AU 715702B	N/A	1998AU-0053068
November 7,	1997	

03/11/2003, EAST Version: 1.03.0007

AU	715702B N/A		Previous	Publ.	AU 9853068
AU	715702B N/A		Based on		WO 9824260
WO	9824260A1 November				1997WO-DE02601
AU	9853068A November	•	N/A		1998AU-0053068
AU	9853068A N/A	•	Based on		WO 9824260
EP	941630A1 November		N/A 1997		1997EP-0949881
EP	941630A1 November	·	N/A		1997WO-DE02601
EP	941630A1 N/A				WO 9824260
CN	1238897A November		N/A 1997		1997CN-0180131

INT-CL (IPC): H04L012/56; H04Q011/04

ABSTRACTED-PUB-NO: DE 19649649A

BASIC-ABSTRACT: The method provides a number of virtual

connections for

transmission of ATM cells over a connecting line, and further connections $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right$

divided into two classes. Class S covers all virtual connections for which the

sigma rule gives significantly better statistical multiplexing than peak cell

rate reservation. Class ${\tt P}$ covers all other virtual connections and especially

those with constant bit rate.

Subdivisions of Class S are defined by a lower or upper limit of peak cell rate and the ratio of sustainable to peak rate. Transmission

and the ratio of sustainable to peak rate. Transmission parameters or their

combinations are stored at a network node and actualised when an ATM link is set up or broken.

ADVANTAGE - ATM cell transmission is more efficient with automatic selection of most favourable class.

CHOSEN-DRAWING: Dwg.0/3

03/11/2003, EAST Version: 1.03.0007

TITLE-TERMS:

ATM LINK STATISTICAL MULTIPLEX METHOD TWO LEVEL CLASSIFY MORE VIRTUAL CONNECT SUBDIVIDED CLASS CHARACTERISTIC MORE FAVOUR RESULT SIGMA RULE ALGORITHM

DERWENT-CLASS: W01

EPI-CODES: W01-A03B1; W01-A06G2;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1998-245705

03/11/2003, EAST Version: 1.03.0007